

COLLABORATE® Live 600



COLLABORATE® Live solutions are the most versatile video collaboration room systems of their kind in the market. COLLABORATE Live 600 is a complete video collaboration system that delivers crystal-clear full duplex audio and high-quality video, perfect for mid-sized meeting rooms.

- > Two CHAT 150 speakerphones that daisy-chain to provide crystal-clear audio clarity.
- > One UNITE® 200 PTZ camera with 1080p60, 12x optical zoom to capture all participants in the room.
- > User interface as intuitive and simple as familiar mobile or tablet devices.
- > Monitor, control, and audit Versa Pro CT with CONVERGENCE™ unified AV network management software
- > COLLABORATE Space is a powerful collaboration application with a full suite of audio, video, and meeting tools in a persistent space.

Better Together

Includes two CHAT 150 speakerphones that daisy-chain to provide crystal-clear audio clarity.

APPLICATIONS

- Video conferencing
- Audio conferencing
- Cloud video collaboration
- Wireless presentation
- Whiteboard
- Recording and streaming

WORKSPACES

- Boardrooms
- Conference rooms



Easy to Use

Unique interface that's as intuitive and simple as familiar tablets and mobile devices.

Great Ideas Need to Be Seen - and Heard!™

COLLABORATE® Live 600

COLLABORATE LIVE 600

- COLLABORATE Live 600 codec appliance
- UNITE 200 PTZ HD camera
- CHATAAttach 150 speakerphone solution
- Power supplies, cables and accessories
- COLLABORATE Space application (90 days)
- 4-way SIP/H.323 MCU license, upgradable to 9-way
- Wireless presentation licenses (1-User) , upgradeable to 6-users.
- One-year support and maintenance with warranty

COLLABORATE LIVE 600 CODEC APPLIANCE

- Video inputs: 2x HDMI (SIP/H.323, Skype for Business), 2x USB
- Video outputs: 1x HDMI, 1x Display port
- Audio inputs: Balanced audio, USB, Line in
- Audio outputs: Balanced audio, Line out, HDMI
- Dimensions: 17 x 8 x 2 ½ (L x W x H)

UNITE 200 CAMERA

- 12x Optical zoom
- 73° wide-angle view with auto-focus
- USB 3.0, HDMI, & IP output
- Full HD 1080p60
- Control: Remote control, USB (UVC), RS-232
- Pan/Tilt Angles: ±170°, Tilt: -30° to +90°

VIDEO CHARACTERISTICS

- Resolution up to 1080p @ 60 fps
- H.261, H.263, H.263+/++
- H.264/AVC High Profile – up to 6Mbps
- H.264/SVC (Skype for Business)

AUDIO STANDARDS

- 20KHz: AAC-LD
- 14KHz: G.722.1 Annex C
- 7KHz: G.722, G.722.1
- 3.4KHz: G.711, G.723.1, G.728, G.729, AMR (3G)

DATA CHARACTERISTICS

- H.239 support for data sharing
- Resolution up to 1080p
- Data inputs via HDMI, Wireless, USB

RECORDING

- Formats: MP4, WMV
- Storage options: Local, external, network (NAS)

STREAMING

- Format: RTSP – Unicast and multicast streaming
- Max number of viewers (unicast): 20
- Max number of viewers (multicast): Depends on network

CONTROL

- Remote control
- Web-based management and control
- Telnet API for 3rd-party control
- AMX and Crestron modules

PART NUMBER

- 930-3001-602

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

Tech Support

Tel: 801.974.3760
tech.support@clearone.com