

# MP7300X-08 Aggregation Router

## Datasheet

### Overview

At the cloud calculation and mobile interconnection times with the fast increasing of the service traffic, the development trend of the customer service diversifying and network flattening makes the aggregation capability requirement of the network for the router higher. High reliability, high performance, high density, high security, and green are the urgent requirements of the customer for the aggregation router. Based on the customer requirements, Maipu launch the new-generation centralized service aggregation router MP7300X-08.

MP7300X-08 aggregation router is the next generation version of MP7300 series which was widely deployed in many countries.

MP7300X-08 supports Dual Control Engine Slots, One Service Engine Slot, 8\*RM4B Slots, Dual AC Power Slots, One Fan Slot.



MP7300X-08

### Highlights

- High speed WAN & LAN interfaces
- Buy as growing SPU engine design
- Dual Control Engines
- Full Modular Design
- Rich software features
- Advanced VPN services
- Complete management modes

# Key Features

- **Flexible uplink link**

MP7300X-08 aggregation router support four kinds of high-performance SPU module which integrates 8 gigabit fixed WAN interfaces, customers do not need to configure additional WAN module; meanwhile, MP7300X-08 uplink supports various mainstream WAN access link technologies, such as 1G/10G Ethernet, E1/CE1, POS/CPOS and V.35 serial line.

- **More than eight expansion slots**

MP7300X-08 aggregation router is modular design which has rich expansion slots. The whole device supports 8 extended slots totally. The strong expansion ability can provide high-density access and protect customer investment. All the modules of MP7300X-08 support hot-swap.

- **High performance**

MP7300X-08 aggregation router reaches more than 8M-60Mpps forwarding performance and the configured ACL, QoS, have small influence for the forwarding performance. And customer can also upgrade the performance by changing SPU service engines.

- **Advanced Secure service**

MP7300X-08 aggregation router has the VPN function and can be connected to the VPDN private channel of the enterprise based on 3G/4G network. Meanwhile, the device data can be transmitted in the secure MPLS/VPLS, IPsec, GRE, L2TP tunnel, preventing the data from being accessed and tampered and providing the higher security for the application over the network.

- **Rich software features**

MP7300X-08 aggregation router provides rich software features; supports various application technologies, such as IPv4/IPv6, VPN, MPLS, multicast, ACL, MAC address binding, access control, bandwidth limitation, MSTP, and NAT; supports RSVP resource reserving protocol and CAR; provides hierarchical QoS function to ensure the high priority of the key services; support the queue management policies, such as FIFO, PQ, CQ, FQ, WFQ, CBWFQ, and LLQ.

- **Rich Management modes**

MP7300X-08 aggregation router supports complete management modes, including SNMPv1/v2c/v3, CLI, USB drive deployment, MIB, RMON, SYSLOG, TR069, IPFIX, etc. Combine with Maipu SNMP Management Platform, it can provide the simple and easy-to-use remote network management.

# Product Specifications

Hardware specification		MP7300X-08			
CPU Processor	1.5GHZ Dual Core				
USB2.0 Port	1				
Console Port (RJ45)	1				
USB2.0 Port	1				
SD Slot	1				
SPU Module	SPU05	SPU10	SPU20	SPU40	
Throughput Performance	8Mpps	15Mpps	25Mpps	55Mpps	
Memory	4G	4G	4G	4G	
Flash	8G	8G	8G	8G	
Fixed WAN interface	8GE Combo	8GE Combo	8GE Combo	8GE Combo	
SPU Slots	1				
RM4B Service Slots	8				
Power Supply Slots	2				
Fan Slot	1				
Dimension W*D*H(mm)	440mm*436mm*222mm (4U)				
Input voltage	AC 100-240V Or DC -48V				
Temperature	Work temperature: 0 – 45°C				
	Storage temperature: -40 – 70°C				
Humidity	Work humidity: 5%-85%				
	Storage humidity: 5%-90%				
Power Consumption	≤500W				
Cooling	Forced air cooling				
Software features					
Link-layer protocol	DDR, PPP, Frame-Relay, Bridge, HDLC, PPPoE, Port isolation, VALN, loopback detection, Error-Disable, MSTP, SPAN, LLDP				
TCP/IP Protocol	DHCP, DHCPv6, DDNS/DNS, NAT/NAT64				
Routing protocol	Static Route/Static Routev6, RIP/RIPng, OSPFv2/OSPFv3, BGP/BGP4+, IS-IS/IS-ISv6, IRMP, PBR				
Security	Support ACL security filtering, PPP encryption, SSH, CPU protection, port security, AAA, IKE, PKI, 802.1X, URFP				
VPN	MPLS, LDP, L2VPN, L3VPN, MPLS QoS, MPLS OAM, 6PE, GRE/GREv6, IPIP, L2TP, L2TPv3, VRF				
QoS	FIFO, PQ, FQ, WFQ, CBWFQ, LLQ, RSVP, CAR, H-QoS, traffic shaping, Rate Limitation				
Multicast	IGMP, MLD, PIM-SM/SSM, PIM-DM/SDM PIMv6-SM/SSM, MSDP, MVPN, NG-MVPN				
Reliability	Backup interface, VRRP/VRRPv3, VBRP, Track, BFD/BFDv6				
Management & Monitoring	Keepalive gateway, NTP, Mirroring, RMON, CWMP, CLI, SSH, WEB, SNMP V1/V2/V3, Telnet, PING, Trace Route, Login, FTP, TFTP, TR069, IPFIX traffic monitoring, IP-SLA				

# Order Information

Host model	Description
<b>MP7300X-08 Host</b>	
MP7300X-08-MF	MP7300X-08-MF Chassis, two control engine slots, one service engine slot, eight-line card slots, one Fan slot, two power slots.
RM3D-MPU	RM3D-MPU Control engine, one CON/AUX/mini-USB port, one Management LAN port, one CMM port, one USB port, one SD Slot.
RM3D-SPU05	RM3D-SPU05 Service Engine, integrate 8GE Combo WAN Port (3/7/8 Slots are high-speed slots)
RM3D-SPU10	RM3D-SPU10 Service Engine, integrate 8GE Combo WAN Ports (3/7/8 Slots are high-speed slots)
RM3D-SPU20	RM3D-SPU10 Service Engine, integrate 8GE Combo WAN Ports
RM3D-SPU40	RM3D-SPU40 Service Engine, integrate 8GE Combo WAN Ports
AD500-15005E	AC Power Module, 500W, 100-240V AC Input, 12V/42A, Hot swap
DD500M-5S0B	DC Power Module, 500W, 40-57V DC Input, 12V/42A, Hot swap
FAN-4B-01	FAN-4B-01, Fan Module for MP7300X-08-MF
<b>Multi-functional module</b>	
RM4B Module	Description
RM4B-H-1POS-OC3	One-port 155M OC3 POS Module
RM4B-H-4POS-OC3	Four-port 155M OC3 POS Module
RM4B-H-1CPOS-OC3	One-port 155M Channelized POS Module
RM4B-H-2CPOS-OC3	Two-port 155M Channelized POS Module
RM4B-H-4SA	Four-port V.35 Serial Module
RM4B-H-8E1	Eight-port E1 Module
RM4B-H-8CE1	Eight-port channelized E1 Module
RM4B-H-8GEF	Eight-port 1000M SFP Fiber Ethernet Module
RM4B-H-8GET	Eight-port 100/1000M Base-T Ethernet Module
RM4B-H-1POS-OC12	One-port 622M OC12 POS Module (SPU05/10 Available for slot 3/7/8)
RM4B-H-2POS-OC12	Two-port 622M OC12 POS Module (SPU05/10 Available for slot 3/7/8)
RM4B-H-4POS-OC12	Four-port 622M OC12 POS Module (SPU05/10 Available for slot 3/7/8)
RM4B-H-1POS-OC48	One-port 2.5G OC48 POS Module (SPU05/10 Available for slot 3/7/8)
RM4B-DH-20GET	20-port 100/1000M Base-T Ethernet Module (SPU05/10 Available for slot 3/7/8)
RM4B-DH-20GEF	20-port 1000M SFP Fiber Ethernet Module (SPU05/10 Available for slot 3/7/8)
RM4B-H-1XGEF	One-port 10G SFP+ Module (SPU05/10 Available for slot 3/7/8)
RM4B-H-4XGEF	Four-port 10G SFP+ Module (SPU05/10 Available for slot 3/7/8)

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

*Maipu Communication Technology Co., Ltd*

No.288, Tianfu 3rd Street

Hi-Tech Zone

Chengdu, Sichuan Province

P. R. China

610041

Tel: (86) 28-65544850,

**Fax:** (86) 28-65544948,

**URL:** [http:// www.maipu.com](http://www.maipu.com)

**Email:** [overseas@maipu.com](mailto:overseas@maipu.com)

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.