

Panomera® Air Blast Charger 4

Compressed air system for wiperless and remote controlled cleaning of the front glass of up to four Panomera® S 4/8 with Mountera® Quick-Lock System



The innovative **Panomera® Air Blast System** is designed for easy, reliable and cost-effective maintenance of the latest **Panomera® S 4 and 8 models**. The compressed air nozzles in the front frames are optimally matched to the front glass and allow gentle cleaning with a concentrated blast of compressed air.

Connection

The **Panomera® Air Blast Charger 4** allows the connection of up to four Panomera® S 4/8 over one compressed air line each. The compressed air line is offered with a length of 25 m or 50 m and can be quickly and easily shortened to the required length.

Compressed air

The **Panomera® Air Blast Charger 4** is equipped with a pressure tank which can be filled with approximately 8 bar compressed air in about one minute. After cleaning a Panomera® with a blast of compressed air, the system is ready for use again in the shortest time, allowing all connected Panomera® systems to be cleaned in just a few minutes.

Control

The **Panomera® Air Blast Charger 4** is equipped with an Ethernet interface and can be remote controlled with minimal effort. Apart from the cyclical safety inspection, no further measures are required at the installation site of the Panomera® systems.

Cleaning

The innovative **Panomera® Air Blast System** generates a targeted compressed air blast which reliably removes water droplets, dust, flying sand or spider webs from the front glass. Unlike conventional systems with wipers, no mechanical wear has to be considered. In addition, the risk of mechanical damage to the glass surface is basically eliminated.

Scope of delivery

- Panomera® Air Blast Charger 4
- Bracket for mounting on walls

Options

- Bracket for mounting on poles
- Compressed air line 25 m or 50 m
- Panomera® Air Blast Kit

Panomera® Air Blast Charger 4

Compressed air system for wiperless and remote controlled cleaning of the front glass of up to four Panomera® S 4/8 with Mountera® Quick-Lock System

System



007896

Panomera® Air Blast Charger 4

Supply system for compressed air for cleaning of the front glass of up to four Panomera® S 4/8 with Mountera® Quick-Lock System, compressed air line optional, compressed air approx. 8 bar, vandal-resistant, powder-coated, grey

Pole Mount Bracket



008239

Panomera® ABC Pole Adapter

Adapter for mounting the Panomera® Air Blast Charger 4 on round (Ø 40 - 170 mm) or rectangular (□ 50 - 150 mm) poles, 2x profile rails (sheet steel), 2x tensioning straps (stainless steel), galvanized

Compressed Air Line



008237

Panomera® ABC Compressed Air Line 25 m

Compressed air line for connecting a Panomera® S 4/8 with Air Blast Kit to a Panomera® Air Blast Charger 4, polyethylene, UV-resistant and flexible, black, length 25 m



008238

Panomera® ABC Compressed Air Line 50 m

Compressed air line for connecting a Panomera® S 4/8 with Air Blast Kit to a Panomera® Air Blast Charger 4, polyethylene, UV-resistant and flexible, black, length 50 m

Upgrade Kit



007899

Panomera® Air Blast Kit

Upgrade kit for a Panomera® S 4/8 with Mountera® Quick-Lock System for cleaning the front glass with compressed air, compressed air line with length 3 m for connection to a Panomera® Air Blast Charger 4 included

Panomera® Air Blast Charger 4

Compressed air system for wiperless and remote controlled cleaning of the front glass of up to four Panomera® S 4/8 with Mountera® Quick-Lock System

General Data	
Supported systems	Up to four Panomera® S 4/8 with Mountera® Quick-Lock System
Length pressure lines	Up to 10 m
Compressed air pressure	Approx. 8 bar (116 PSI)
Connections	
Ethernet	1× RJ45, 10BASE-T/100BASE-TX PoE
Electrical Data	
Voltage supply	115-230 V AC ±5%, 50/60 Hz
Power consumption	Max. 200 W
Thermal output	Max. 682 BTU/h
Mechanical Data	
Dimensions (W × H × D)	Approx. 400 × 500 × 210 mm (15.7" × 19.7" × 8.3")
Weight	Approx. 21.0 kg (46 lb)
Material	Steel
IK protection	IK10
IP rating	IP66
Finish	Epoxy polyester powder
Color	Light grey (RAL 7035 ¹⁾)
Environmental Conditions	
Installation sites	Indoor and outdoor
Temperature	-30°C up to +60°C (-22°F – 140°F)
Humidity	0 – 90% RH, non-condensing
Approvals and Certifications	
Type	CE

1) The color of the powder coating may differ slightly from the RAL color indicated. This is due to production and does not constitute a defect.

Dallmeier electronic GmbH & Co.KG | Bahnhofstr. 16, 93047 Regensburg, Germany | +49 941 8700-0 | dallmeier.com

All trademarks identified by * are registered trademarks of Dallmeier electronic GmbH & Co.KG.

Third-party trademarks are named for information purposes only. Dallmeier electronic respects the intellectual property of third parties and always attempts to ensure the complete identification of third-party trademarks and indication of the respective holder of rights. In case that protected rights are not indicated separately, this circumstance is no reason to assume that the respective trademark is unprotected.

Specifications subject to change without notice. Errors and misprints excepted. Pictures may differ from the actual product.

