



DAHUA

Video Conferencing Introduction2023

309078



Display system

Audio system

Smart whiteboard

Video conference system

Conference discussion system

Smart conference control system

Server: The equipment that provides computing services for terminals is the equipment at the core of the network in the computer network.

MCU



LAN

Network protocol: A set of rules, standards, or conventions established for data exchange in a computer network.

Terminal: The most peripheral device in the system network



Endpoint



Moscow




Endpoint



Saint Petersburg


Endpoint to MCU: all to one
MCU to other endpoints: one to all
Coding and decoding works on MCU

MCU (MultiPoint Control Unit)



- √: 1. All participants see the audio and video at the same time
- 2. Various codec devices are compatible
- ×: The pressure on the MCU server is high, requiring high configuration

SFU(Selective Forwarding Unit)



Coding and decoding works on codec

√: 1. Reduced delay and improved real-time performance

2. The CPU resource consumption is reduced, and the concurrency is greater under the same server configuration conditions

3. The resolution is adaptive according to the network bandwidth on each site

×: Conference consistency and stability are affected by each terminal capability and network

Product family

Conference platform



MCU with plug-in server
DH-VCS-MCU95F0-4K



Business board
DH-VCS-MCU95F-4K



MCU
DH-VCS-MCU95B0

Cloud-based



public cloud, on premise

HD endpoint



Conference codec
DH-VCS-TS52A0



All-in-one endpoint
DH-VCS-TS51A0



All-in-one endpoint
DH-VCS-TS20A0

Software-elink



Conference camera



HDMI Conference camera
DH-VCS-C7A0



4K Dual-eye tracking camera
XC900

Coming soon



UHD Conference camera
XC800



USB PTZ camera
DH-VCS-C5B0



USB Sound bar
DH-VCS-C5A0



2K Minibar
(Auto Framing)



All-in-one USB
Camera
DH-VCS-C4B0



2K Webcam
(Auto Focus)
HTI-UC340

Mic & speaker



Omnidirectional Microphone
DH-VCA-MCA400



Omnidirectional Microphone
DH-VCA-MCA450



Ceiling microphone system

USB camera



USB Webcam
HT-UC320



USB webcam
HT-UC325



1080P Webcam
HTI-UC300



3 Lens Sound bar



Coming soon

Features| convenient operation



Various type

- ✓ Schedules
- ✓ Start now
- ✓ Recurring
- ✓ Room paired



Speaker highlight


- ✓ Voice recognition
- ✓ Automatic switching

Conference management

- Conference sites control: **Professional**
- Operation: **convenient**

Up to **60** picture separate mode


Features| Smart collaboration




Screen sharing



Program sharing



Whiteboard



Data and content sharing


Understand each others



Audience collaboration



Smart Network **adaptability**, Build excellent **meeting experience**



Resolution **self-adaption**, ensure smooth conference experience

Features| Web center control

- Support accounts, address lists, organization management
- Support conference scheduling and establishing (members/time/materials/endpoints/security/recurrent meeting/conference template, etc.)
- Support in-conference management(endpoints control/layout switch/sharing/collaboration, etc.)
- Support third-party integration

Advanced settings like: Encrypted meetings

One-click start meeting


QR code invitation

Internal voting


Human face resource library manage

Hybrid conference and live streaming

Local real-time recording and broadcasting



Features| Open and standard



Third-party device test report

This section displays six pages of test reports from various third-party testing institutions. The reports include certificates, technical specifications, and test results, all featuring official seals and stamps.

Standard protocol

- Standard SIP、H.323


Benefit to original system

- Save cost for customer




... ..

Topology| Typical system




DH-VCS-MCU95B0

- 32 sites 1080P@30fps SFU mode
- 10 sites 1080P@30fps MCU mode(Including H.323, SIP)
- H.265、 H.264 HP、 H.264 BP、 H.263 video coding
- End-to-end delay $\leq 300\text{ms}$
- Support group setting to expand capacity



DH-VCS-MCU95F0-4K

- 120+120 sites 1080p@30fps SFU mode
- 48+48 sites 1080p@30fps MCU mode(Including H.323, SIP)
- Supports H.265 video coding.
- ITU-T H.323、 IETF SIP
- 4×HDMI, 2×USB3.0, 1×USB serial port, 1×RJ45 10/100/1000Mbps management, 4×RJ45 10/100/1000Mbps self-adaption port per Business board
- 1+1 Redundancy, Back-up;
- Support group setting to expand capacity
- CE certification



DH-VCS-C7A0+DH-VCS-TS52A0

- H.265 video compression/4K resolution/1080P@60fps dual stream.
- OPUS audio codec, 48KHz sample frequency.
- Supports USB connection. to omnidirectional mic.
- In the event of a 30% packet loss, the conference audio and video is unaffected.
- Multiple video and audio interfaces including HDMI, VGA, 3G-SDI, HDCVI.
- Supports infrared remote control/wireless mouse/keyboard, etc.



CONFERENCE CAMERA-Wider Eyes & Smarter Brain

XC800

HD PTZ camera

4K@30fps, 12x optical zoom

Pan:±120°, Tilt:-30°to 30°

- For ceiling install demand
- For AV conference solution
- For 12-15 people room



VCS-C5B0

All-in-one USB camera

1080p/10x optical zoom

- For price sensitive
- For OEM
- For 8-12 people room



XC900

Tracking PTZ camera

4k@30fps, 16x optical zoom

Pan: -170° to 170°, Tilt:-30° to 30°

- For high quality distributor
- For high-end OEM
- For project bidding
- For 10-18 people room



XC800-NDI

All-in-one USB camera

NDI –faster,smooth and more stable for long distance connection and transmission




DH-VCS-TS51A0


- Integrated design, built-in HD camera/codec, small and elegant.
- 1080P@60fps, 12x optical zoom, 73° horizontal field of view.
- H.265 video compression/4K resolution/dual stream/1080P auxiliary stream.
- OPUS audio codec, 48KHz sample frequency.
- Supports omnidirectional mic (USB) /infrared remote control/wireless mouse/keyboard, etc.
- Horizontal mount/wall mount/ceiling mount.



[Interface and connection]



[Interface and connection]



WEBCAM-Stronger & More Diverse

Capability upgrade
Cover all you want



Good video partner

- Auto framing +Auto Focus
- Camera+Speaker+Microphone, All-in-one solution

Create your real time meeting

- Smooth Privacy Cover+2 stands+ 4m Omnidirectional Mic= Close to reality
- 4K +8MP+120° view = Reproduce reality
- Auto framing + Auto WB= Better than reality

ALL-IN-ONE CAMERA-One Stop Solution

VCS-C4B0



Microphone

Speaker

LED Light




Function Keys

- Camera On/Off
- Volume Down/Up
- Mute

1080P Camera

USB Type-C

- 1080P FHD image sensor
- 100° Ultra wide angle (horizontal)
- 99% AI noise reduction/AEC/ANS/AGC, strong double speak inhibition
- Built-in 4-element omnidirectional microphone array, 4 - 6m pickup distance
- High-quality wideband speaker
- Compatibility with mainstream software
- USB2.0 Type-C connection, Plug & Play
- Aesthetic design, fashionable and simple



ALL-IN-ONE CAMERA-One Stop Solution



High Compatibility
Zoom, Teams, Skype, etc.

USB Plug & Play
Multiple connection
USB type-C, HDMI, Bluetooth

Ultra Wide Angle
The 120° ultra wide FOV+15° PTZ

Speaker Tracking
Auto-Framing

UHD Resolution
The 8MP CMOS sensor



AI Noise Reduction
8W Speaker

Built-in 4 BF Microphone
6 Meters Pick-up Distance

MIC & SPEAKER

VCS-MCA450

Enjoy your time with friends and music


- For brand OEM
- For IT personal market
- fashion appearance
- For price sensitive customer
- For discussion and chat
- --excellent microphone and audio



VCS-MCA400

Create your value in collaboration and meeting

- For IT conference market
 - For quality sensitive customer
 - Business style appearance
- Support cascade expansion distance



MIC & SPEAKER


Ceiling microphone DH-HAM400D

DSP DH-HAA400-EN


Wall-mounted speaker DH-HAS400W-20W

Ceiling speaker DH-HAS400C-20W

Controller DH-HAA400C



Embedded installation



Ceiling installation



Product Features

- 91-Element Microphone Array
- 12 Deep Side lobe Beamforming
- 8m effective Pickup Range
- Daisy-Chain Up To 8 Devices
- AI Noise-Suppression
- True Full Duplex
- Digital Signal Processing (DSP)

Product Value

- Solve the problem of unstable signal on wireless microphone, when the scene is larger and the environment is more complex
- Hub with audio processor and amplifier, be able to adapt to existing sound reinforcement system
- High gross profit per product
- Better value-added space for installation services



What we should know about projects



Please confirm with us about the BOQ and solution before send it to customer!

1. Customer background like: their project experience, their business relationship, the core decision maker, etc.
2. The project background like: budget, actual requirement(not only devices), project type
3. The competitors
4. Project feasibility information, Bandwidth, point location, concurrency, functional items, networking, etc

Our support


1. Project proposal, solution topology
2. Pre-sales consulting and testing
3. MCU deployment and endpoints maintain support (user manual/operation guide and online remote support)
4. Big project functionality customization
5. Real machine operation training (under certain conditions)



Web cloud conference platform manageme...




Offline platform operation guide.pptx




DH-VCS-MCU95 F0-4K_Datasheet.pdf



【elink】 video conference mobile app.pdf



【elink】 video conference PC software client.pdf



Video conference system introduction 202307.pptx



DH-VCS-MCU95 F0-4K user manual.docx

Industry



Government



Business

Education



Healthcare

.....

Government



Remote communication



Emergency command



Remote court trial



Remote visitation in prison

Business



Remote Collaboration



Daily conference



Online interview



Online training



Enterprise emergency meeting

Education



Remote learning



Live stream class



Online seminar



Parents remote visit and communication

Healthcare



Remote consultation



Surgical training



Emergency command



Remote ward rounds